



EZ FIX MANUAL URETHANE REPAIR SYSTEM



Available as a kit.

EZ Fix is a two-part, 100% solids urethane compounded for the repair of rubber and PVC conveyor belts and linings.

FEATURES

- Excellent for conveyor belt repair, pulley repairs, skirt board damage, covering fasteners and cleat repair
- Odor free and non toxic
- Chemical and abrasion resistant in most applications
- The material cures to touch in 2 minutes and can be buffed after two hours
- 100% solids means NO shrinkage and NO VOC's, making it safe to use
- Shelf life is 1 year unopened, good for up to 60 days after opening
- Standard system is self-leveling
- A high viscosity version is available (NS - Non Sag)
- Packed in 2 x 200 ml, two-part cartridges and uses a dual plunger dispensing gun
- The special mixing tips have a baffle system that mixes the material as it is dispensed
- Covers 6.35 mm x 6.35 mm x 6 m

EZ FIX MANUAL URETHANE REPAIR SYSTEM

PRODUCT CODE	DESCRIPTION
EF-BR-200KIT	EZ Fix Kit: dispensing unit, 6 cartridges: 200 x 200 ml, 12 mixing tips
EF-BR-200SL	EZ Fix dual cartridge: 200 x 200 ml, 1 mixing tip
EF-MT-1	EZ Fix mixing tip
EF-MT-12	EZ Fix refill mixing tip: 12 pieces
EF-DG-430	EZ Fix dispensing gun
EF-EZPC-50ML	EZ Fix Primer: 50 ml size
EF-EZPC-100ML	EZ Fix Primer: 100 ml size
EF-EZPC-250ML	EZ Fix Primer 250 ml size

EZFIX MANUAL URETHANE PROPERTIES	
Colour	Black
Elastomer	Polyurethane
Elongation at Break	110%
Hardness	60 Shore A
Abrasion Resistance	200 mg / 1000 cycles
Tensile Strength	1630 psi / 115 kg / cm ²



Note: The above data is based on extensive testing and represents standard values. Shaw Almex Industries reserves the right to make changes without prior notice and refuses all claims arising from such changes. All items are subject to change without previous notice.